

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: Wolfe, <i>et al.</i>	) Title: Electric motor
	)
Serial No.: 10/662,683	) Group Art Unit: 3729
	)
Filed: September 15, 2003	) Examiner: T.D. Phan

TRANSMITTAL OF CORRECTED CLAIMS APPENDIX

*Commissioner for Patents*  
*P.O. Box 1450*  
*Alexandria, Virginia 22313-1450*


On November 24, the applicant was mailed a copy of a paper from the Board of Patent Interferences that ordered the examiner to notify the applicant to file a paper that corrects the claims appendix. A corrected appendix is attached.

Please advise the undersigned if anything else is needed.

Respectfully submitted,

MARSHALL, GERSTEIN & BORUN LLP  
Suite 6300 Sears Tower  
Chicago, Illinois 60606-6357  
(312) 474-6300

By:

  
Richard M. LaBarge  
Reg. No. 32,254

December 11, 2008

## APPENDIX A

### Claims Involved in the Appeal of Application Serial No. 10/662,683

11. A method of making an electric motor, comprising:

winding a first magnet wire about a first lug in a winding board and a first protrusion in a stator, the winding board being disposed on the stator and including a switch having at least an internal terminal, and a fuse having an input terminal and an exit terminal;

laying the first magnet wire across the exit terminal and the input terminal on the fuse;

connecting an end portion of the first magnet wire directly to the switch; and

severing the first magnet wire between the input terminal and the exit terminal on the fuse.

12. The method of claim 11, further comprising routing the first magnet wire along the winding board under clips.

13. The method of claim 11, wherein the switch includes an internal terminal and an external terminal, the internal terminal includes a first block and a second block, and the first magnet wire is terminated on the first block.

14. The method of claim 13, wherein the first block and the second block include tang terminals and the first magnet wire is fused to the tang of the first block by welding.

15. The method of claim 11, wherein the input terminal and the exit terminal include tangs, and the first magnet wire is fused to the tangs by welding.

16. The method of claim 11, further comprising winding the first magnet wire about the first lug in the winding board and the first protrusion in the stator to form a first pole.

17. The method of claim 11, further comprising winding a second magnet wire about a second lug in the winding board and a second protrusion in the stator to form a second pole.

18. The method of claim 17, further comprising disposing the end of the second magnet wire on the second block of the internal terminal.

19. The method of claim 18, further comprising fusing the second magnet wire to the tang of the second block by welding.